

NON-ROTATING TUBE STAND WITH TRANSVERSE

Eight-foot rails and platform mount are standard. Options include ten foot rails, twelve foot rails, 6" trunnion rings, and 6 3/4" trunnion rings.

TRAVEL AND ALIGNMENT

Longitudinal travel of focal spot	78 7/8" for 8 ft. rail 102 7/8" for 10 ft. rail 126 7/8" for 12 ft. rail
Transverse travel of focal spot	± 5" from detent position
Vertical travel of focal spot (Standard T.B.)	73" max, 15 5/8" min.
Range of trunnion motion	+82°, -15° (with standard collimator)
Angulation	360°
Wall to focal spot at detent position	37 1/8"

MOUNTING SPECIFICATIONS

Minimum ceiling height	91 1/4" wall mount or ceiling mount
Wall/Ceiling mounting bolt specification	Minimum pull-out force of 500 lbs. each
Floor mounting bolt location	Minimum pull-out force of 500 lbs. each

ELECTRICAL

24 VDC, 2 Amp to come from D164 power supply (included) or generator.

SHIPPING INFORMATION

CONTENTS	DIMENSIONS	WEIGHT
Complete Column	97 x 43 x 8 inches	245 lbs.
Rails	8 x 9 x 96 inches	40 lbs.

Specifications subject to change without notice.

NON-ROTATING TUBE STAND WITH TRANSVERSE S114

